



Receptacles 0.5 - 6 mm²

■ Data: brass, tin plated.

mm ²	Cat. no.	mm e	t	L	For tabs	s	Pcs/ pack	Rec. tool
0,5-1	B1003FLS5	6,0	0,25	14,0	2,8x0,5	7	100	DRB0115
	B1003FLS8	5,0	0,3	12,7	2,8x0,8	7	100	DRB0115
0,75-1,5	B1505FLS5-1	6,4	0,4	16,0	4,8x0,5	7	100	GRB0560
	B1505FLS8-1	6,4	0,4	16,0	4,8x0,8	7	100	GRB0560
	B1507FLS1	7,6	0,4	19,0	6,3x0,8	7	100	GRB0560
1,5-2,5	B2505FLS5	6,0	0,35	15,6	4,8x0,5	8	100	GRB0560
	B2505FLS8	6,0	0,4	16,0	4,8x0,8	8	100	GRB0560
	B2507FLS1	7,6	0,4	19,0	6,3x0,8	8	100	GRB0560
4-6	B4607FLS1	7,6	0,4	19,0	6,3x0,8	8	100	GRB0560

t = palm thickness s = strip length

Receptacles with locking lip 0.5 - 6 mm²

■ Data: brass, tin plated.

mm ²	Cat. no.	mm e	t	L	For tabs	s	Pcs/ pack	Rec. tool
0,5-1,5	B1507FLSN	7,5	0,4	19,2	6,3x0,8	7	100	GRB0560
1,5-2,5	B2507FLSN	7,5	0,4	19,0	6,3x0,8	8	100	GRB0560
4-6	B4607FLSN	7,5	0,4	19,0	6,3x0,8	9	100	GRB0560

t = metal thickness s = strip length

Multiple tabs 0.5 - 2.5 mm²

■ Data: brass, tin plated.

mm ²	Cat. no.	mm e	t	L	For tabs	s	Pcs/ pack	Rec. tool
0,5-1,5	B1507FLSH	8,0	0,4	20,0	6,3x0,8	7	100	GRB0560
1,5-2,5	B2507FLSH	8,0	0,4	20,0	6,3x0,8	7	100	GRB0560

t = metal thickness s = strip length

Receptacle, 90°, 0.5 - 1.5 mm²

■ Data: brass, tin plated.

mm ²	Cat. no.	mm e	t	L	For tab	s	Pcs/ pack	Rec. tool
0,5-1,5	B1507FLSB8	7,7	0,4	13,0	6,3x0,8	7	100	TRB0515B

t = metal thickness s = strip length

Receptacle 90°, 0.5 - 1 mm²

■ Data: brass, tin plated.

mm ²	Cat. no.	mm e	t	L	For tabs	s	Pcs/ pack	Rec. tool
0,5-1	B1003FLSV5	4,9	0,3	9,3	2,8x0,5	7	100	DRB0115

t = metal thickness s = strip length

For detailed information regarding recommended tool, see tool section at the end of this chapter.