



Pre-insulated TWIN end terminals 2x0.5 - 2x10 mm², ET2, standard colour

■ Data: electrolytic copper, tin plated. CSA approved.

■ Polypropylene insulation, colour code according to

DIN 46228. Designed to connect two conductors in one terminal.



	AWG	mm ²	Cat. no.	mm d	H/D	L ₁	L	s	Pcs/pack	Rec. tool*
	2 x 20	2 x 0,5	A0,5-6ET2	1,5	2,4/4,6	6	13,0	8	100	EEB0160
			A0,5-8ET2	1,5	2,4/4,6	8	15,0	10	100	EEB0160
	2 x 20	2 x 0,75	A0,75-8ET2	1,8	2,7/5,4	8	15,0	10	100	EEB0160
			A0,75-10ET2	1,8	2,7/5,4	10	17,0	12	100	EEB0160
			A0,75-12ET2	1,8	2,7/5,4	12	19,0	14	100	EEB0160
■	2 x 18	2 x 1	A1-8ET2	2,05	3,3/5,3	8	15,0	10	100	EEB0160
			A1-10ET2	2,05	3,3/5,3	10	17,0	12	100	EEB0160
			A1-12ET2	2,05	3,3/5,3	12	19,0	14	100	EEB0160
■	2 x 16	2 x 1,5	A1,5-8ET2	2,3	3,5/6,5	8	16,0	10	100	EEB0160
			A1,5-12ET2	2,3	3,5/6,5	12	20,0	14	100	EEB0160
■	2 x 14	2 x 2,5	A2,5-10ET2	2,9	4,1/7,7	10	18,5	12	100	EEB0160
			A2,5-13ET2	2,9	4,1/7,7	13	21,5	15	100	EEB0160
■	2 x 12	2 x 4	A4-12ET2	3,8	4,9/8,7	12	23,0	14	100	GEB4010C-TWIN/ EEB0160
			A4-18ET2	3,8	4,9/8,7	18	29,0	20	100	GEB4010C-TWIN/ EEB0160
■	2 x 10	2 x 6	A6-14ET2	4,9	6,1/9,9	14	25,0	16	100	GEB4010C-TWIN/ EEB0160
			A6-18ET2	4,9	6,1/9,9	18	29,0	20	100	GEB4010C-TWIN/ EEB0160
■	2 x 8	2 x 10	A10-14ET2	6,5	7,1/12,9	14	26,0	16	100	GEB4010C-TWIN

s = strip length

* Use die nest marked closest to the total cross section area in the terminal

For detailed information regarding recommended tool, see tool section at the end of this chapter.



Pre-insulated TWIN end terminals 2x0.5 - 2x10 mm², ETT2, alternative colour

- Data: electrolytic copper, tin plated. CSA approved. Polypropylene insulation, colour code type T.
- Designed to connect two conductors in one terminal.



	AWG	mm ²	Cat. no.	mm d	H/D	L ₁	L	s	Pcs/pack	Rec. tool*
	2 x 20	2 x 0,5	A0,5-6ETT2	1,5	2,4/4,6	6	13,0	8	500	EEB0160
			A0,5-8ETT2	1,5	2,4/4,6	8	15,0	10	500	EEB0160
■	2 x 20	2 x 0,75	A0,75-8ETT2	1,8	2,7/5,4	8	15,0	10	500	EEB0160
			A0,75-10ETT2	1,8	2,7/5,4	10	17,0	12	500	EEB0160
			A0,75-12ETT2	1,8	2,7/5,4	12	19,0	14	500	EEB0160
■	2 x 18	2 x 1	A1-8ETT2	2,05	3,3/5,3	8	15,0	10	500	EEB0160
			A1-10ETT2	2,05	3,3/5,3	10	17,0	12	500	EEB0160
			A1-12ETT2	2,05	3,3/5,3	12	19,0	14	500	EEB0160
■	2 x 16	2 x 1,5	A1,5-8ETT2	2,3	3,5/6,5	8	16,0	10	500	EEB0160
			A1,5-12ETT2	2,3	3,5/6,5	12	20,0	14	500	EEB0160
■	2 x 14	2 x 2,5	A2,5-10ETT2	2,9	4,1/7,7	10	18,5	12	250	EEB0160
			A2,5-13ETT2	2,9	4,1/7,7	13	21,5	15	250	EEB0160
■	2 x 12	2 x 4	A4-12ETT2	3,8	4,9/8,7	12	23,0	14	100	GEB4010C-TWIN/ EEB0160
			A4-18ETT2	3,8	4,9/8,7	18	29,0	20	100	GEB4010C-TWIN/ EEB0160
■	2 x 10	2 x 6	A6-14ETT2	4,9	6,1/9,9	14	25,0	16	100	GEB4010C-TWIN/ EEB0160
			A6-18ETT2	4,9	6,1/9,9	18	29,0	20	100	GEB4010C-TWIN/ EEB0160
■	2x8	2 x 10	A10-14ETT2	6,5	7,1/12,9	14	26,0	16	100	GEB4010C-TWIN

s = strip length * Use die nest marked closest to the total cross section area in the terminal

Pre-insulated TWIN end terminals 2x0.5 - 2x10 mm², ETW2, alternative colour

- Data: electrolytic copper, tin plated. CSA approved. Polypropylene insulation, colour code type W.
- Designed to connect two conductors in one terminal.

	AWG	mm ²	Cat. no.	mm d	H/D	L ₁	L	s	Pcs/pack	Rec. tool*
■	2 x 20	2 x 0,5	A0,5-6ETW2	1,5	2,3/4,5	6	13,0	8	100	EEB0160
			A0,5-8ETW2	1,5	2,3/4,5	8	15,0	10	100	EEB0160
	2 x 20	2 x 0,75	A0,75-8ETW2	1,8	2,6/5,1	8	15,0	10	100	EEB0160
			A0,75-10ETW2	1,8	2,6/5,1	10	17,0	12	100	EEB0160
			A0,75-12ETW2	1,8	2,6/5,1	12	19,0	14	100	EEB0160
■	2 x 18	2 x 1	A1-8ETW2	2,0	3,0/5,1	8	15,0	10	100	EEB0160
			A1-10ETW2	2,0	3,0/5,1	10	17,0	12	100	EEB0160
			A1-12ETW2	2,0	3,0/5,1	12	19,0	14	100	EEB0160
■	2 x 16	2 x 1,5	A1,5-8ETW2	2,3	3,5/6,4	8	16,0	10	100	EEB0160
			A1,5-12ETW2	2,3	3,5/6,4	12	20,0	14	100	EEB0160
■	2 x 14	2 x 2,5	A2,5-10ETW2	2,9	4,0/7,5	10	18,5	12	100	EEB0160
			A2,5-13ETW2	2,9	4,0/7,5	13	21,5	15	100	EEB0160
■	2 x 12	2 x 4	A4-12ETW2	3,8	4,9/8,6	12	23,0	14	100	GEB4010C-TWIN/ EEB0160
			A4-18ETW2	3,8	4,9/8,6	18	29,0	20	100	GEB4010C-TWIN/ EEB0160
■	2 x 10	2 x 6	A6-14ETW2	4,6	5,8/9,6	14	25,0	16	100	GEB4010C-TWIN/ EEB0160
			A6-18ETW2	4,6	5,8/9,6	18	29,0	20	100	GEB4010C-TWIN/ EEB0160
■	2 x 8	2 x 10	A10-14ETW2	6,5	7,0/12,6	14	26,0	16	100	GEB4010C-TWIN

s = strip length * Use die nest marked closest to the total cross section area in the terminal

For detailed information regarding recommended tool, see tool section at the end of this chapter.

