



CFTV - HEAT SHRINK CABLE SLEEVE


Heat shrink tubing and adhesive liner combination that established the CATV industry standard for splice and connector protection.

FEATURES AND BENEFITS

- Craft friendly installation
- Exceptional split resistance
- CFTV adhesive retains bond providing long term protection
- Except for clear or transparent tubing, all colors are UV resistant
- Selective strippability to meet CATV industry specifications
- Minimal heat required to produce error free installation without splitting
- Thermochromatic lines change color to signal waterproof seal
- Shrinks and seals in half the time of alternative products
- Shrink ratio: 3:1
- Continuous operating temperature: -55°C to 110°C
- Shrink temperature: 120°C min.

TYPICAL APPLICATIONS

- Strain relief of coaxial connections
- Waterproof protection of CATV connectors



3:1
SHRINK RATIO

-55°C to 110°C
(-67°F to 230°F)
CONTINUOUS OPERATING
TEMPERATURE

MARKETS:

Industrial


STANDARDS:



Heat shrink cable sleeve

DIMENSIONS

ORDER NUMBER	EXPANDED		RECOVERED				APPLICATION RANGE		DELIVERY UNITS
	Internal Diameter (min) D		Internal Diameter (max) d		Total Wall Thickness (nom) W		General Use		Lengths
	MM	IN	MM	IN	MM	IN	MM	IN	1.22 M / 48 IN
0400	10.2	0.40	3.8	0.15	2	0.08	4.5 - 8.5	.18 - .34	75
0750	19.0	0.75	5.6	0.22	2	0.08	6.0 - 16.5	.24 - .65	35
1100	27.9	1.10	10.2	0.40	2	0.08	11.5 - 25.0	.45 - 1.0	75
1300	33.0	1.30	10.2	0.40	2	0.08	11.5 - 30.0	.45 - 1.2	60
1500	38.1	1.50	12.7	0.50	2	0.08	14.0 - 35.0	.55 - 1.4	40
1700	43.2	1.70	12.7	0.50	2	0.08	14.0 - 40.0	.55 - 1.6	40
2050	52.1	2.05	19.0	0.75	2	0.08	21.0 - 45.0	.82 - 1.8	25
2750	69.8	2.75	25.4	1.00	2	0.08	30.0 - 63.0	1.2 - 2.5	15



ORDERING

Select a dimension which will shrink snugly over the application to be covered. If recovery is restricted the resultant wall thickness will be less than specified.

- Please specify the product name, order number and options you require
- *Example:* CFTV, 1700, lined

Please contact your Customer Service Representative for information on custom colors, sizes, lengths and material data sheet.

FOR FURTHER INFORMATION, PLEASE CONTACT:

Americas: 800 422 6872

Canada: 800 845 6808

Asia Pacific: +86 512 82280099

Europe: +49 2226 9047 355

All information contained in this datasheet is believed to be reliable. We advise however that customers should separately evaluate the suitability of our products for their particular application. Shawcor gives no guarantees in respect to accuracy or sufficiency of the information presented and disclaim any liability regarding its use. Our responsibilities are only those listed in our Standard Terms and Conditions of Sale for these products. In no instance will we be liable for any eventual, indirect, or consequential damage or damages arising from the sale, resale, transfer, use or misuse of the product. Subject to modification.

DSG-CANUSA PRODUCTS | dsgcanusa.com

Version: 03 2021/OCT/06

 **SHAWCOR**